






Smart Line interactive UPS Simulated Sinewave

SM10 Series
(650-3000VA)



- Fully intelligent line Line-interactive UPS with VI technology.
- AVR buck and boost technology to auto-stabilise voltage fluctuations and extend battery life.
- LCD graphical display for easy and accurate monitoring.
- Double protection for overload / short circuit & Over voltage.
- Smart communications USB and RJ-11/45 ports, interface cables and monitoring software included.
- Cold start function with auto-restart facility.
- Microprocessor based design. Compact design.
- UPS Auto on when AC back.
- Off mode charging.
- Compatible with Windows, Linux, SCO UNIX and DOS.
- Intelligent battery management and fast charging.
- Wide input voltage range .
- Auto restart when mains power is restored.
- Safety shutdown: system alarm and auto Power-Off by USB interface communicating with PC

Technical Specifications

MODEL	SM10 650	SM10 1200	SM10 1500	SM10 2000	SM10 3000
Rated power	650VA / 390W	1200VA / 720W	1500VA / 900W	2000VA / 1200W	3000VA / 1800W
Input AC voltage	(100/110/120Vac or 220/230/240 Vac) $\pm$ 5Vac				
Input Voltage Range	100 / 110 / 120 V: 80 ~ 150 Vac; 220 / 230 / 240 V: 162 ~ 295 Vac (145 ~ 295 Vac optional)				
Frequency input range	50 Hz / 60 Hz (auto-sense), 50 Hz / 60 Hz $\pm$ 5% ~ 10%				
Inverter output range	100 / 110 / 120 Vac $\pm$ 10% or 220 / 230 / 240 Vac $\pm$ 10%				
Output Frequency (Line)	50 / 60 Hz $\pm$ 1% (auto-sensing)				
Waveform	Mains mode: pure sinewave; Battery mode: simulated sine wave				
Inverter Efficiency	Max. 75%		Max. 80%	Max. 81%	Max. 85%
Generator connection	Available (generator input power is settable)				
Transfer time	Typical 8 ms, 10 ms max				
Batteries Number	12 V / 7 Ah x1	12 V / 7 Ah x 2	12 V / 8 Ah x 2	12 V / 9 Ah x 2	12 V / 9 Ah x 4
Battery charging	8 hrs. to fully charged / 6 hrs. to 90% charged				
Charging current	1 A				
Rated DC Voltage	12V	24V	24V	24V	48V
THD resistive load	$\leq$ 5%				
Short circuit	Auto protection. Output shuts off and The buzzer beeps continuously.				
Overload Inverter load	110% for 60 s, 125% for 10 s, 150% for 5 s (shut down directly)				
Protections	Overload, short circuit (inverter), battery low voltage, battery overcharge, over temperature				
Operating temperature	0°C~40°C				
Operating humidity	0-90% RH @ 0- 40°C (non-condensing)				
Noise	$\leq$ 35dB(1m from front panel)				
Output Socket	IEC or Schuko*				
Communication	USB & RJ45 (standard), dry contacts / SNMP (optional)				
Network protection	RJ45/11 surge protector				
Dimensions (W x D x H) (mm)	100 x 290x140	140 x 345 x 170		125 x 380 x 225	170 x 400 x 250
Net weight (kg)	5	9	10	14	20

DALTON

Dalton Power (UK) Ltd | Unit 3 Narberth Bridge Business Park Narberth SA67 8RF | United Kingdom
 Tel: +44 (0) 190 557 0358 Fax: +44 (0) 183 445 0092 Email: info@daltonpower.co.uk
www.daltonpower.co.uk

